



Leading Through Innovation



HSS-E

COUNTERBORES

FLACHSENKER

- For Machining Screw Head Seats
- Zur Herstellung von Schraubenkopfsenkungen

SELECTION GUIDE



SERIES	EL950		
TYPE	MEDIUM	FINE	BEFORE THREADING
PILOT DIA.	3.4~14.0	3.2~13.0	2.5~10.2
CUTTER DIA.	6.0~20.0		
PAGE	443		

SURFACE TREATMENT

Bright

HSS-E COUNTERBORES

For Machining Screw Head Seats



Please visit globalyg1.com/mat for material search

◎ : Excellent ○ : Good

Recommended cutting conditions : P.445

ISO	VDI 3323	Material Description	Composition / Structure / Heat Treatment	HB	HRc		
P	1	Non-alloy steel	About 0.15% C Annealed	125		◎	
	2		About 0.45% C Annealed	190	13	◎	
	3		About 0.45% C Quenched & Tempered	250	25	◎	
	4		About 0.75% C Annealed	270	28	◎	
	5		About 0.75% C Quenched & Tempered	300	32	◎	
	6	Low alloy steel	Annealed	180	10	◎	
	7		Quenched & Tempered	275	29	◎	
	8		Quenched & Tempered	300	32	◎	
	9		Quenched & Tempered	350	38	○	
	10		High alloyed steel, and tool steel	Annealed	200	15	◎
	11			Quenched & Tempered	325	35	○
M	12	Stainless steel	Ferritic / Martensitic Annealed	200	15		
	13		Martensitic Quenched & Tempered	240	23		
	14	Austenitic	180	10			
K	15	Grey cast iron	Pearlitic / ferritic	180	10		
	16		Pearlitic (Martensitic)	260	26		
	17	Nodular cast iron	Ferritic	160	3		
	18		Pearlitic	250	25		
	19	Malleable cast iron	Ferritic	130			
	20		Pearlitic	230	21		
N	21	Aluminum-wrought alloy	Not Curable	60		○	
	22		Curable Hardened	100		○	
	23	Aluminum-cast, alloyed	≤ 12% Si, Not Curable	75		○	
	24		≤ 12% Si, Curable Hardened	90		○	
	25		> 12% Si, Not Curable	130			
	26	Copper and Copper Alloys (Bronze / Brass)	Cutting Alloys, PB>1%	110			
	27		CuZn, CuSnZn (Brass)	90			
	28		CuSn, lead-free copper and electrolytic copper	100			
	29	Non Metallic Materials	Duroplastic, Fiber Reinforced Plastic				
	30		Rubber, Wood, etc.				
S	31	Heat Resistant Super Alloys	Fe Based	Annealed	200	15	
	32			Cured	280	30	
	33		Annealed	250	25		
	34		Ni or Co Based	Cured	350	38	
	35			Cast	320	34	
	36	Titanium Alloys	Pure Titanium	400 Rm			
	37		Alpha + Beta Alloys	Hardened	1050 Rm		
H	38	Hardened steel	Hardened	550	55		
	39		Hardened	630	60		
	40	Chilled Cast Iron	Cast	400	42		
	41	Hardened Cast Iron	Hardened	550	55		



COUNTERBORES

EL950 SERIES

HSS-E, 3 FLUTE COUNTERBORES for 180° CAPSCREW


● HSS-E, 3 SCHNEIDEN FLACHSENKER MIT FESTEM FÜHRUNGZAPFEN

● FRAISES À LAMER HSS-E 3 DENTS TÊTE DE VIS À 180°

● LAMATORI A TRE TAGLIENTI IN HSS-E per sedi di viti a testa cilindrica a 180°

► The counterbores with solid pilot are designed for machining as fillister screw caps or ejector caps in molds.

► Die Flachsenker mit festem Führungzapfen dienen dem 180° Ansenken für Zylinderkopfschrauben und Auswerferstiften in Formen



HSS-E

DIN 373

3

PLAIN



P.445

MEDIUM

Unit : mm

EDP No.	ITEM No.	Screw Size	Pilot Diameter	Cutter Diameter	Shank Diameter	Overall Length
PLAIN	PLAIN		D(e8)	D1(z9)	D2(h9)	L
EL950003	YG54M3-M	M3	3.4	6.0	5	71
EL950035	YG54M3.5-M	M3.5	3.9	6.5	5	71
EL950004	YG54M4-M	M4	4.5	8.0	5	71
EL950005	YG54M5-M	M5	5.5	10.0	8	80
EL950006	YG54M6-M	M6	6.6	11.0	8	80
EL950008	YG54M8-M	M8	9.0	15.0	12.5	100
EL950010	YG54M10-M	M10	11.0	18.0	12.5	100
EL950012	YG54M12-M	M12	14.0	20.0	12.5	100

FINE

Unit : mm

EDP No.	ITEM No.	Screw Size	Pilot Diameter	Cutter Diameter	Shank Diameter	Overall Length
PLAIN	PLAIN		D(e8)	D1(z9)	D2(h9)	L
EL950901	YG54M3-F	M3	3.2	6.0	5	71
EL950902	YG54M3.5-F	M3.5	3.7	6.5	5	71
EL950903	YG54M4-F	M4	4.3	8.0	5	71
EL950904	YG54M5-F	M5	5.3	10.0	8	80
EL950905	YG54M6-F	M6	6.4	11.0	8	80
EL950906	YG54M8-F	M8	8.4	15.0	12.5	100
EL950907	YG54M10-F	M10	10.5	18.0	12.5	100
EL950908	YG54M12-F	M12	13.0	20.0	12.5	100

►NEXT PAGE

◎ : Excellent ○ : Good

ISO	P										M			K							
	Non-alloy steel					Low alloy steel					High alloyed steel, and tool steel			Stainless steel			Grey cast iron		Nodular cast iron		Malleable cast iron
Material Description	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	
HRC	13	13	25	28	32	10	29	32	38	15	35	15	23	10	10	26	3	25	21	21	
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230	
Recommended	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	


ISO	N					S										H					
	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys					Titanium Alloys		Hardened steel	Chilled Cast Iron	Hardened Cast Iron	
Material Description	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41
HRC	60	100	75	90	130	110	90	100			15	30	25	38	34			55	60	42	55
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400Rm	1050Rm	550	630	400	550
Recommended	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎

HSS-E, 3 FLUTE COUNTERBORES for 180° CAPSCREW

- HSS-E, 3 SCHNEIDEN FLACHSENKER MIT FESTEM FÜHRUNGSPFENNEN
- FRAISES À LAMER HSS-E 3 DENTS TÊTE DE VIS À 180°
- LAMATORI A TRE TAGLIANTI IN HSS-E per sedi di viti a testa cilindrica a 180°

► The counterbores with solid pilot are designed for machining as fillister screw caps or ejector caps in molds.

► Die Flachsenker mit festem Führungspfen dienen dem 180° Ansenken für Zylinderkopfschrauben und Auswerferstiften in Formen



HSS-E
DIN 373
3
PLAIN
P.445

BEFORE THREADING

Unit : mm

EDP No.	ITEM No.	Screw Size	Pilot Diameter D(e8)	Cutter Diameter D1(z9)	Shank Diameter D2(h9)	Overall Length L
PLAIN	PLAIN					
EL950909	YG54M3-T	M3	2.5	6.0	5	71
EL950910	YG54M3.5-T	M3.5	2.9	6.5	5	71
EL950911	YG54M4-T	M4	3.3	8.0	5	71
EL950912	YG54M5-T	M5	4.2	10.0	8	80
EL950913	YG54M6-T	M6	5.0	11.0	8	80
EL950914	YG54M8-T	M8	6.8	15.0	12.5	100
EL950915	YG54M10-T	M10	8.5	18.0	12.5	100
EL950916	YG54M12-T	M12	10.2	20.0	12.5	100

Tolerances according to DIN 7160 & 7161
Toleranzen nach DIN 7160 & 7161

Nominal-Diameter in mm / Nennmaßbereich in mm					Nominal-Diameter in mm / Nennmaßbereich in mm				
	from 1 to 3 von 1 bis 3	over 3 to 6 über 3 bis 6	over 6 to 10 über 6 bis 10	over 10 to 18 über 10 bis 18		from 6 to 10 von 6 bis 10	over 10 to 14 über 10 bis 14	over 14 to 18 über 14 bis 18	over 18 to 24 über 18 bis 24
Tolerance range in μm / Toleranzwerte in μm					Tolerance range in μm / Toleranzwerte in μm				
e8	- 14 - 28	- 20 - 38	- 25 - 47	- 32 - 59	z9	+ 78 + 42	+ 93 + 50	+ 103 + 60	+ 125 + 73
h9	0 - 25	0 - 30	0 - 36	0 - 43					

◎ : Excellent ○ : Good

ISO	P										M						K						
	Non-alloy steel					Low alloy steel					High alloyed steel, and tool steel						Stainless steel		Grey cast iron		Nodular cast iron		Malleable cast iron
Material Description	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20			
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20			
HRc	13	25	28	32	10	29	32	38	15	35	15	23	10	10	26	3	25						
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230			
Recommended	◎	◎	◎	◎	◎	◎	◎	◎	○	◎	○												

ISO	N										S						H						
	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys						Titanium Alloys		Hardened steel		Chilled Cast Iron		Hardened Cast Iron
Material Description	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41		
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41		
HRc	60	100	75	90	130	110	90	100			15	30	25	38	34			55	60	42	55		
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400Rm	1050Rm	550	630	400	550		
Recommended	○	○	○	○																			

EL950 SERIES

HSS-E, 3 FLUTE COUNTERBORES for 180° CAPSCREW

Vc = m/min.
fz = mm/tooth
RPM = rev./min.
FEED = mm/min.

ISO	VDI 3323	Material Description	Parameter	Cutter Diameter (Ø)							
				6.0	6.5	8.0	10.0	11.0	15.0	18.0	20.0
P	1	Non-alloy steel	Vc	25	25	25	25	25	25	25	25
			fz	0.08	0.08	0.08	0.11	0.11	0.11	0.13	0.13
			RPM	1326	1224	995	796	723	531	442	398
			FEED	322	297	242	258	234	172	167	150
			Vc	24	24	24	24	24	24	24	24
	2		fz	0.08	0.08	0.08	0.11	0.11	0.11	0.13	0.13
			RPM	1273	1175	955	764	694	509	424	382
			FEED	309	286	232	248	225	165	160	144
			Vc	18	18	18	18	18	18	18	18
	3		fz	0.08	0.08	0.08	0.11	0.11	0.11	0.13	0.13
			RPM	955	881	716	573	521	382	318	286
FEED		232	214	174	186	169	124	120	108		
Vc		18	18	18	18	18	18	18	18		
4	fz	0.08	0.08	0.08	0.11	0.11	0.11	0.13	0.13		
	RPM	955	881	716	573	521	382	318	286		
	FEED	232	214	174	186	169	124	120	108		
	Vc	18	18	18	18	18	18	18	18		
5	fz	0.08	0.08	0.08	0.11	0.11	0.11	0.13	0.13		
	RPM	955	881	716	573	521	382	318	286		
	FEED	232	214	174	186	169	124	120	108		
	Vc	24	24	24	24	24	24	24	24		
6	fz	0.08	0.08	0.08	0.11	0.11	0.11	0.13	0.13		
	RPM	1273	1175	955	764	694	509	424	382		
	FEED	309	286	232	248	225	165	160	144		
	Vc	18	18	18	18	18	18	18	18		
7	fz	0.08	0.08	0.08	0.11	0.11	0.11	0.13	0.13		
	RPM	955	881	716	573	521	382	318	286		
	FEED	232	214	174	186	169	124	120	108		
	Vc	18	18	18	18	18	18	18	18		
8	fz	0.08	0.08	0.08	0.11	0.11	0.11	0.13	0.13		
	RPM	955	881	716	573	521	382	318	286		
	FEED	232	214	174	186	169	124	120	108		
	Vc	15	15	15	15	15	15	15	15		
9	fz	0.08	0.08	0.08	0.11	0.11	0.11	0.13	0.13		
	RPM	796	735	597	477	434	318	265	239		
	FEED	193	178	145	155	141	103	100	90		
	Vc	24	24	24	24	24	24	24	24		
10	fz	0.08	0.08	0.08	0.11	0.11	0.11	0.13	0.13		
	RPM	1273	1175	955	764	694	509	424	382		
	FEED	309	286	232	248	225	165	160	144		
	Vc	18	18	18	18	18	18	18	18		
11	fz	0.08	0.08	0.08	0.11	0.11	0.11	0.13	0.13		
	RPM	955	881	716	573	521	382	318	286		
	FEED	232	214	174	186	169	124	120	108		
	Vc	30	30	30	30	30	30	30	30		
21	fz	0.08	0.08	0.08	0.11	0.11	0.11	0.13	0.13		
	RPM	1592	1469	1194	955	868	637	531	477		
	FEED	382	353	286	315	286	210	207	186		
	Vc	30	30	30	30	30	30	30	30		
22	fz	0.08	0.08	0.08	0.11	0.11	0.11	0.13	0.13		
	RPM	1592	1469	1194	955	868	637	531	477		
	FEED	382	353	286	315	286	210	207	186		
	Vc	20	20	20	20	20	20	20	20		
23	fz	0.08	0.08	0.08	0.11	0.11	0.11	0.13	0.13		
	RPM	1061	979	796	637	579	424	354	318		
	FEED	255	235	191	210	191	140	138	124		
	Vc	20	20	20	20	20	20	20	20		
24	fz	0.08	0.08	0.08	0.11	0.11	0.11	0.13	0.13		
	RPM	1061	979	796	637	579	424	354	318		
	FEED	255	235	191	210	191	140	138	124		



HEAD OFFICE

211, Sewolcheon-ro, Bupyeong-gu, Incheon, South Korea

Phone: +82-32-526-0909

Http://www.yg1.kr E-mail: yg1@yg1.kr

Note The information is provided for reference only. Tool specifications are subject to change without prior notice.
Although we endeavor to supply accurate and timely information, there can be no guarantee to cover every particular application.
YG-1 or publishers are not liable for any damage for use of the information.



Search 'YG-1' on social media outlets